

DUCHESNE COUNTY MONUMENT SURVEY RECORD


T1S R3W

1/4

SEC 28 SEC 27

U.S.B.&M.

G-13



SCALE: 1"=30'



FOUND A REBAR WITH A 2½" ALUMINUM DUCHESNE COUNTY MONUMENT AT SECTION CORNER

NAIL AND WASHER ON EAST SIDE OF POWER POLE

NAIL AND WASHER ON NORTH SIDE OF CORNER POST

SET A 5/8" REBAR WITH A 1½" ALUMINUM CAP AT 1/4 CORNER

NAIL AND WASHER ON NORTH SIDE OF CORNER POST

FOUND ALUM CAP ON 5/8" REBAR AT 1/16 CORNER

NAIL AND WASHER ON SOUTH SIDE OF CORNER POST

NAIL AND WASHER ON SOUTH SIDE OF CORNER POST

FOUND A TRI STATE ALUMINUM CAP AT SECTION CORNER

NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40°21'33.88695"N AND LONG. 110°13'06.20894"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND A 5/8" REBAR IN THE ROAD AT THE POSITION OF THE 1/4 CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET A 5/8"x24" REBAR WITH A 2½" ALUMINUM DUCHESNE COUNTY MONUMENT AT THE POSITION OF THE 1/4 CORNER AFTER ROAD CONSTRUCTION



STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)
NAD83 UTAH CENTRAL ZONE
N: 7304846.395
E: 1997518.743
NAVD88 EL: 6210.5'

LATITUDE: 40°21'59.99279" N
LONGITUDE: 110°13'06.16240" W
ELLIPSOID HEIGHT: 6156.67'
(GEOID 03 CONUS)
PUBLIC LAND SURVEY SYSTEM GCDB ID NO.
UT300010S0030W0_400240



CERTIFICATION

I Jerry D. Allred, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 28 FEB 2018

Jerry D. Allred, Professional Land Surveyor
Certificate No. 148951
Duchesne County Surveyor

